

Approved For Release 2001/07/27 : CIA-RDP81B00679R001000030122-7

14 DEC 1960

DOCUMENT NO. _____
 NO CHANGE IN CLASS. **X**
 VI. SPECIAL NOTES
 1. 1/2/82 19 8 8
 2. 1/2/82 19 8 8
 3. 1/2/82 19 8 8
 4. 1/2/82 19 8 8
 5. 1/2/82 19 8 8
 6. 1/2/82 19 8 8
 7. 1/2/82 19 8 8
 8. 1/2/82 19 8 8
 9. 1/2/82 19 8 8
 10. 1/2/82 19 8 8
 11. 1/2/82 19 8 8
 12. 1/2/82 19 8 8
 13. 1/2/82 19 8 8
 14. 1/2/82 19 8 8
 15. 1/2/82 19 8 8
 16. 1/2/82 19 8 8
 17. 1/2/82 19 8 8
 18. 1/2/82 19 8 8
 19. 1/2/82 19 8 8
 20. 1/2/82 19 8 8
 21. 1/2/82 19 8 8
 22. 1/2/82 19 8 8
 23. 1/2/82 19 8 8
 24. 1/2/82 19 8 8
 25. 1/2/82 19 8 8
 26. 1/2/82 19 8 8
 27. 1/2/82 19 8 8
 28. 1/2/82 19 8 8
 29. 1/2/82 19 8 8
 30. 1/2/82 19 8 8
 31. 1/2/82 19 8 8
 32. 1/2/82 19 8 8
 33. 1/2/82 19 8 8
 34. 1/2/82 19 8 8
 35. 1/2/82 19 8 8
 36. 1/2/82 19 8 8
 37. 1/2/82 19 8 8
 38. 1/2/82 19 8 8
 39. 1/2/82 19 8 8
 40. 1/2/82 19 8 8
 41. 1/2/82 19 8 8
 42. 1/2/82 19 8 8
 43. 1/2/82 19 8 8
 44. 1/2/82 19 8 8
 45. 1/2/82 19 8 8
 46. 1/2/82 19 8 8
 47. 1/2/82 19 8 8
 48. 1/2/82 19 8 8
 49. 1/2/82 19 8 8
 50. 1/2/82 19 8 8
 51. 1/2/82 19 8 8
 52. 1/2/82 19 8 8
 53. 1/2/82 19 8 8
 54. 1/2/82 19 8 8
 55. 1/2/82 19 8 8
 56. 1/2/82 19 8 8
 57. 1/2/82 19 8 8
 58. 1/2/82 19 8 8
 59. 1/2/82 19 8 8
 60. 1/2/82 19 8 8
 61. 1/2/82 19 8 8
 62. 1/2/82 19 8 8
 63. 1/2/82 19 8 8
 64. 1/2/82 19 8 8
 65. 1/2/82 19 8 8
 66. 1/2/82 19 8 8
 67. 1/2/82 19 8 8
 68. 1/2/82 19 8 8
 69. 1/2/82 19 8 8
 70. 1/2/82 19 8 8
 71. 1/2/82 19 8 8
 72. 1/2/82 19 8 8
 73. 1/2/82 19 8 8
 74. 1/2/82 19 8 8
 75. 1/2/82 19 8 8
 76. 1/2/82 19 8 8
 77. 1/2/82 19 8 8
 78. 1/2/82 19 8 8
 79. 1/2/82 19 8 8
 80. 1/2/82 19 8 8
 81. 1/2/82 19 8 8
 82. 1/2/82 19 8 8
 83. 1/2/82 19 8 8
 84. 1/2/82 19 8 8
 85. 1/2/82 19 8 8
 86. 1/2/82 19 8 8
 87. 1/2/82 19 8 8
 88. 1/2/82 19 8 8
 89. 1/2/82 19 8 8
 90. 1/2/82 19 8 8
 91. 1/2/82 19 8 8
 92. 1/2/82 19 8 8
 93. 1/2/82 19 8 8
 94. 1/2/82 19 8 8
 95. 1/2/82 19 8 8
 96. 1/2/82 19 8 8
 97. 1/2/82 19 8 8
 98. 1/2/82 19 8 8
 99. 1/2/82 19 8 8
 100. 1/2/82 19 8 8
 101. 1/2/82 19 8 8
 102. 1/2/82 19 8 8
 103. 1/2/82 19 8 8
 104. 1/2/82 19 8 8
 105. 1/2/82 19 8 8
 106. 1/2/82 19 8 8
 107. 1/2/82 19 8 8
 108. 1/2/82 19 8 8
 109. 1/2/82 19 8 8
 110. 1/2/82 19 8 8
 111. 1/2/82 19 8 8
 112. 1/2/82 19 8 8
 113. 1/2/82 19 8 8
 114. 1/2/82 19 8 8
 115. 1/2/82 19 8 8
 116. 1/2/82 19 8 8
 117. 1/2/82 19 8 8
 118. 1/2/82 19 8 8
 119. 1/2/82 19 8 8
 120. 1/2/82 19 8 8
 121. 1/2/82 19 8 8
 122. 1/2/82 19 8 8
 123. 1/2/82 19 8 8
 124. 1/2/82 19 8 8
 125. 1/2/82 19 8 8
 126. 1/2/82 19 8 8
 127. 1/2/82 19 8 8
 128. 1/2/82 19 8 8
 129. 1/2/82 19 8 8
 130. 1/2/82 19 8 8
 131. 1/2/82 19 8 8
 132. 1/2/82 19 8 8
 133. 1/2/82 19 8 8
 134. 1/2/82 19 8 8
 135. 1/2/82 19 8 8
 136. 1/2/82 19 8 8
 137. 1/2/82 19 8 8
 138. 1/2/82 19 8 8
 139. 1/2/82 19 8 8
 140. 1/2/82 19 8 8
 141. 1/2/82 19 8 8
 142. 1/2/82 19 8 8
 143. 1/2/82 19 8 8
 144. 1/2/82 19 8 8
 145. 1/2/82 19 8 8
 146. 1/2/82 19 8 8
 147. 1/2/82 19 8 8
 148. 1/2/82 19 8 8
 149. 1/2/82 19 8 8
 150. 1/2/82 19 8 8
 151. 1/2/82 19 8 8
 152. 1/2/82 19 8 8
 153. 1/2/82 19 8 8
 154. 1/2/82 19 8 8
 155. 1/2/82 19 8 8
 156. 1/2/82 19 8 8
 157. 1/2/82 19 8 8
 158. 1/2/82 19 8 8
 159. 1/2/82 19 8 8
 160. 1/2/82 19 8 8
 161. 1/2/82 19 8 8
 162. 1/2/82 19 8 8
 163. 1/2/82 19 8 8
 164. 1/2/82 19 8 8
 165. 1/2/82 19 8 8
 166. 1/2/82 19 8 8
 167. 1/2/82 19 8 8
 168. 1/2/82 19 8 8
 169. 1/2/82 19 8 8
 170. 1/2/82 19 8 8
 171. 1/2/82 19 8 8
 172. 1/2/82 19 8 8
 173. 1/2/82 19 8 8
 174. 1/2/82 19 8 8
 175. 1/2/82 19 8 8
 176. 1/2/82 19 8 8
 177. 1/2/82 19 8 8
 178. 1/2/82 19 8 8
 179. 1/2/82 19 8 8
 180. 1/2/82 19 8 8
 181. 1/2/82 19 8 8
 182. 1

100-1157
page 2

(c) The original D-20 compressor, which revealed exceptional performance during calibration without blade or disc vibration did not have tip shrouding but did have solid rim dampers.

(d) The apparent need for tip shrouding was initiated earlier with the P-2 engine which had neither tip shrouding or rim damping. This engine revealed excessive disc vibration.

(e) Due to blade vendor lead time the tip shrouding was not incorporated in the original compressor (paragraph 3c) but was incorporated in the latest compressor as a matter of course.

(f) Based upon the success of the original D-20 compressor (paragraph 3c), P & W proposed action is to remove the tip shrouding and change to solid rim dampers.

The above will cause some delay in compressor development. It is now expected that this delay will be absorbed and will not be reflected in Z or Y engine deliveries.

It is expected that the solid rim dampers, if fabricated from costly austenitic, will be limited to 75 hours operation at [REDACTED]. The tubular rim dampers were intended to be limited to 300 hours at [REDACTED]. 75 hours at [REDACTED] is not an attractive limitation and must be improved before a TBO of 100 hours may be realized.

25X1D

25X1D

25X1D

4. The engine bill of material weight status as of 16 November 1960 is as follows:

(a)	<u>Weight (lbs)</u>	<u>Cumulative changes relative to "Y" Engine. Spec. Weight of 5657 lbs.</u>
Current eng. Estimate	5679	+222
Cat. 1 Changes Outstanding	-136	+ 36
Cat. 2 Changes Outstanding	- 87	- 51
Cat. 3 Changes Outstanding	- 22	- 73

(b) Since the last weight status report (ref. (b) memorandum), P & W has initiated a change in weight

SECRET

SECRET

000-1157

Page 3

accounting. Now, completed design changes are not reflected in the "Current Engine Estimate" until after final project approval. Before, they were included upon completion before final approval. Based upon the "old" system, the current engine estimate tabulated above would read 5734 rather than 5879.

(c) Due to this change in accounting the engine bill of material will not reflect the spec. weight of 5657 lbs. by 30 December 1960, as presented at the Supplier's Meeting of 28 September 1960. It is expected that the bill of material will reflect a weight of 5740 lbs. by 30 December 1960.

5. It has been agreed between Lockheed, P & W, and Ashland Refineries that the 3.5 psia vapor pressure at 300°F as required by Lockheed will be incorporated into fuel spec. FWA-523. A corresponding inspection procedure also will be incorporated which will tend to penalize the fuel at the 50 psia vapor pressure point. This inspection procedure has been accepted reluctantly by Ashland who feels that some additional blending will be required in order to meet the 50 psia point. Upon release, the revised spec. will be presented to Esso and Shell for their comment.

25X1A

SECRET

Development Branch
000-1157

DPD/DB/TCO:rew
Distribution:

- 1-DD/P
- 2-C/DB/DPD
- 3-AC/DPD
- 4-C/TAS/DPD
- 5-DPD/DB
- 6-DPD/DB
- 7-DPD/RI